



REGULAR GRATINGS



Tootekood	Kõrgus	Suurus	M2	ORTHO	IFR	ISO	VIN	CFR	ESD
12.5 1220 3658	12,5	1220 x 3658 mm	4,5	x	x				

15 1220 3660	15	1220 x 3660 mm	4,5	x	x			x	x
--------------	----	----------------	-----	---	---	--	--	---	---

25 1000x2000	25	1000 x 2000 mm	2,0	x	x			x	x
25 1007x2007		1007 x 2007 mm	2,0	x	x				
25 1000x3000		1000 x 3000 mm	3,0	x				x	x
25 1007x3007		1007 x 3007 mm	3,0	x	x				
25 1000x4038		1000 x 4038 mm	4,0	x	x			x	x
25 1007x4047		1007 x 4047 mm	4,1	x	x				
25 1220x3658		1220 x 3658 mm	4,5	x	x				
25 1220x3660		1220 x 3660 mm	4,5	x	x			x	x

30 1000x2000	30	1000 x 2000 mm	2,0	x	x	x	x	x	x
30 1007x2007		1007 x 2007 mm	2,0	x	x				
30 1000x3000		1000 x 3000 mm	3,0	x	x				x
30 1007x3007		1007 x 3007 mm	3,0	x	x				
30 1000x4038		1000 x 4038 mm	4,0	x	x			x	x
30 1007x4047		1007 x 4047 mm	4,1	x	x				
30 1200x3000		1200 x 3000 mm	3,6			x	x		
30 1220x3658		1220 x 3658 mm	4,5	x	x				
30 1220x3660		1220 x 3660 mm	4,5	x	x				x
30 1225x3660		1225 x 3660 mm	4,5						x

38 1000x2000	38	1000 x 2000 mm	2,0	x	x	x	x	x	x
38 1007x2007		1007 x 2007 mm	2,0	x	x				
38 1000x3000		1000 x 3000 mm	3,0	x	x			x	x
38 1007x3007		1007 x 3007 mm	3,0	x	x				
38 1000x4038		1000 x 4038 mm	4,0	x	x			x	x
38 1007x4047		1007 x 4047 mm	4,1	x	x				
38 1200x3000		1200 x 3000 mm	3,6			x	x		
38 1220x3658		1220 x 3658 mm	4,5	x	x				
38 1220x3660		1220 x 3660 mm	4,5	x	x			x	x
38 1220x4038		1220 x 4038 mm	4,9					x	x

50 1100x2000	50	1100 x 2000 mm	2,2			x	x		
50 1220x3660		1220 x 3660 mm	4,5	x	x			x	x
50 1220x3658		1220 x 3658 mm	4,5	x					
50 1228x3666		1228 x 3666 mm	4,5		x				

ORTHO - Moderate corrosion resistance, IFR - Excellent corrosion resistance and fire retardant properties, ISO - High chemical resistance, VIN - Very high chemical resistance, CFR - Conductive, ESD - Antistatic